

## TurfCare TCA1400

### For the cleaning and maintenance of sand and rubber filled artificial turf surfaces

The ground driven TurfCare TCA1400 from SMG cleans and maintains the surface of sand and rubber filled synthetic turf pitches. The wheel drive makes the equipment independent from any hydraulic or power shaft drives. Therefore the TurfCare can be pulled by various vehicles such as small compact tractors or quads.



The rotary brush straightens up the turf fibres and in the same process, gathers up all kind of dirt particles. The working depth can be precisely set and locked via two adjusting spindles. The two screens act as dirt trays. The vibrating screen can be precisely adjusted with variable settings from 4 - 10 mm depending on the degree of pollution and the grid size of the infilling material.

For the pass of narrow doorways the two transport rollers can be folded out and the tow bar can be raised up. A trailing brush row levels the infilling material and with a gentle action, lightly works it back into the artificial turf.



Drag brush row and draw bar can be fold up



Adjusting spindles for working depth and tow bar



Vibrating screen continuously adjustable from 4 - 10 mm



Fold-out transport rollers for transverse drive



Tines for the gentle loosening of the infill material

**Recommended  
accessories for  
TCA 1400**



**FloorTest FT50**  
Page 87



**Leaves blower**  
Page 86



**Gloves**  
Page 89

<b>Chassis</b>	Laser-cut steel frame construction, plastic-coated
<b>Working Width</b>	1.400 mm
<b>Weight</b>	170 kg
<b>Dimensions</b>	L 1.800 x W 1.800 x H 550 mm

Subject to technical alterations